BIRKAN
Intelligent offset & flexographic materials
SINCE 1924

Offset printing blankets • Blanket conversion • Flexo printing plates • Direct laser engraving • Varnishing plates & blankets • Prepress and repro services • Underpacking materials • 3D printing

Aqua Plus FB 1.95

Compressible premium coating blanket

Aqua Plus FB („fabric base“) was developed for all types of aqueous and UV coatings and is also suitable for the latest types of coatings. Superior results are also achieved with special coatings such as soft-touch, matt or gloss coating.

Like all Tyref coating plates or rubber blankets, Aqua Plus FB is equipped with a special surface technology that prevents the build-up of ink. The coating form can be cut both manually and by CAD plotter. The cutting lines are clearly visible on the rubber surface.

Thanks to a new technology, the adhesive layer has a higher level of adhesion, which proves to be extremely resistant to delamination. Excellent dimensional stability allows multiple use for repeat runs. In addition, the integrated compressible layer ensures high smash resistance and increased durability.

Aqua Plus FB is produced in compliance with REACH and is therefore suitable for use in the manufacture of food packaging.

Recommendations for use:

- Make sure that the cutting blade does not touch the fabric base! The cut should end in the compressible layer.
- Peel gently.
- Please use a compressible underpacking to achieve optimum coating results.
- Apply minimum contact pressure between the Anilox© cylinder and the plate as well as between the plate and impression cylinder.

APPLICATION RANGE:

On-line varnishing ● spot coating ● area coating ● packaging printing

COMPATIBILITY WITH:

Water based (aqueous) coatings ● UV coatings ● special coatings (eg. soft-touch)


MAIN FEATURES:

Excellent varnish transfer ● no ink build-up ● easy stencil preparation manually or by CAD ● sharp and clean cut-out ● extremely high delamination resistance ● very good smash resistance ● high durability ● reusable for repeat runs ● REACH-compliant

TyreF
innovative technology materials for offset and flexo packaging printing

Technical Data

Surface	NBR rubber
Carrier	3-ply fabric
Colour	ochre yellow
Micro Hardness	65° Shore A
Elongation	< 1.5 %
Stencil Depth	0.90 mm
Thickness	1.95 mm
Ref. No.	904013



BIRKAN GmbH • Painhofener Strasse 11 • 82279 Eching am Ammersee • Germany
Telefon +49 (0) 8143 - 9204-0 • Fax +49 (0) 8143 - 9204-24 • info@birkan.de • www.birkan.de
ISO 9001:2015 certified by DSR Certification / Certificate No..QMS-22.11.405

All specifications without garantee and excluding all liability. Subject to modifications.
© BIRKAN 2025